



## CHARACTERISTICS:

- New laser reception technology: precision mm display of the height difference even at large distances
- For use in horizontal or vertical operation
- Protection class IP66
- Very high accuracy
- Plumbing point for marking out right angles
- Automatic height monitoring, stops the laser in the event of strong vibrations

## APPLICATIONS:

- Horizontal leveling
- Vertical leveling

## EVO 360 PROFESSIONAL

### Model

EVO 360 PROFESSIONAL

### Technical details:

Item description	Horizontal/vertical rotation laser
Dimensions	179 x 143 x 211 mm
Leveling	automatic
Measuring tolerance	±0.10 mm/m
Self-leveling range	±5°
Application range without handheld receiver (radius)	20 m*
Application range with handheld receiver (radius)	300 m*
Operating temperature	-10°C to +50 °C
Rotation speed	600 rpm
Tripod adapter	5/8"
Protection class	IP66
Power supply	2 x 3.6 V (18650) Li-ion battery (2 x 3450 mAh)
Operating time (at 20 °C)	40 hrs
Laser class	2M, DIN EN 60825-1:2014+A1:2017
Output power	< 1.0 mW
Wavelength	635 - 650 nm

### Included accessory:

- REC RRD2
- Rechargeable battery cell 18650
- Charger
- Power plug
- EVO 360 case

