



METRON 60 BT PRODUCT DETAILS

HIGHLIGHTS

- Bluetooth interface for data transfer to compatible SOLA Measures app
- > Fold-out end piece for measuring from the outer edges
- > 1/4" thread for fastening on tripod
- > 3-line backlit display for quick reading
- > Soft grip and ergonomic design
- > Automatic switch-off

Applications	
Length measurement	
Area measurement	
Volume measurement	
Min./max. measurement	
Continuous measurement	
Indirect 2-point measurement	
Indirect 3-point measurement	
Addition/subtraction	
Measurement memory	





- 1) The end piece of the METRON 60 BT can be folded out at an angle of 90° and serves as a stop aid for measurements from outer edges.
- 2) If the METRON is used via Bluetooth with the compatible SOLA Measures app, photos or construction plans can be directly dimensioned and measurements can be saved, managed, and shared.











ORDER INFORMATION

Included with delivery

- > METRON 60 BT laser distance meter
- 3.7 V Li-ion battery (850 mAh)
- > USB-C charging cable
- > Belt case
- Strap
- Quick starter



METRON 60 BT	Item no. 71027101
Technical Data	
Measuring range	0.05–60 m*
Accuracy	± 1.5 mm**
Unit of measurement	m, in, ft, ft+in
Laser class	2
Laser type	635 nm < 1 mW
Protection class	IP54
Automatic power off, laser	45 s
Automatic power off, device	180 s
Operating time	up to 5,000 measurements***
Battery type	3.7 V Li-ion battery (850 mAh)
Operating temperature	0°C to 40°C
Storage temperature	-20°C to 60°C
Dimensions (H \times W \times D)	119 × 46 × 28 mm
Weight with batteries	100 g

- * Depending on conditions at work site.
- ** Accurate from 0.05–10 m. The maximum tolerance of 0.1 mm/m may deteriorate at distances between 10 m and 60 m.
- *** Use at room temperature.

OPTIONAL ACCESSORIES

Laser visibility glasses, red LB RED	Item no. 71124501
Magnetic target plate ZS RED	Item no. 71126401
Compact tripod FST	Item no. 71121701
Inclination adapter NK1	Item no. 71128501
MST mini tripod	Item no. 71121901